

4750 & 4710

SHAPERS



A TRADITION OF INNOVATION™



Model 4750 shown

FEATURING

- Cast iron mitre gauge with hold-down
- Locking spindle
- Sliding table (4750 only)
- Large cast iron table
- Reversible spindle
- 5 speed step pulley (3,000-10,000 RPM)
- Heavy cast iron base

The Oliver 4750 & 4710 Shapers are built to dish out whatever profile you need. The 4750 has a sliding table, increasing safety and helping shape those difficult to handle peices. The beefy spindle is reversable and locks, helping you to change a wide variety of cutters quickly. The cast iron miter gauge on both machines has a hold down, too. A five speed step

pulley system gives you a wide range of speeds, from 3,000 to 10,000 RPM. All this powered by a 5HP motor on a heavy cast iron base and you've got a machine built the Oliver way. Flip this sheet over to take a peek inside and find out why the 4750 and 4710 could be right for you...

CALL: 1-800-559-5065
To find a dealer near you!

**2 YEAR
LIMITED
WARRANTY**



4750 & 4710

SHAPERS



4710 SHAPER (shown) is the non-sliding table equivalent of the 4750



ABOVE: THE SLIDING TABLE IN ACTION gives you a stable and smooth platform for your work; the cast-iron miter gauge with hold-down firmly secures the workpiece.

BELOW: CAST IRON MICRO ADJUSTABLE FENCE ASSEMBLY allows you to make the finest adjustments

BOTTOM: FIVE SPEED PULLEY ASSEMBLY allows for a wide range of speeds

| Model | 4710 | 4750 |
|-------------------------------------|--|--|
| Stock No. (5HP, 1Ph) | 4710.001 | 4750.001 |
| Stock No. (5HP, 3Ph) | 4710.002 | 4750.002 |
| Table Dimensions (in.) | 41-1/2 x 29-1/2 | 41-1/2 x 29-1/2 |
| Table Height (in.) | 34-1/4 | 34-1/4 |
| Sliding Table Travel (in.) | n/a | 39-1/2 |
| Sliding Table Size (L x W/in.) | n/a | 41-1/2 x 9 |
| Spindle Speed (RPM) | 3,000, 4,000, 6,000, 8,000, 10,000 | 3,000, 4,000, 6,000, 8000, 10,000 |
| Spindle Direction | Reversible | Reversible |
| Vertical Spindle Adjustment(in.) | 5 | 5 |
| Maximum Tool Height (in.) | 5 | 5 |
| Maximum Tool Diameter (in.) | 8-1/2 | 8-1/2 |
| Spindle Diameter (in.) | 1-1/4 | 1-1/4 |
| Dust Collector Port Diameter (in.) | 4 | 4 |
| Minimum CFM Required | 800 | 800 |
| Motor | 5HP, 1Ph, 220V only or 5HP, 3Ph, 230/460V, Prewired 230V | 5HP, 1Ph, 230V only or 5HP, 3Ph, 230/460V, Prewired 230V |
| Shipping Dimensions (L x W x H/in.) | 45 x 38 x 42 | 45 x 38 x 42 |
| Gross Weight (lbs.) | 950 | 1,050 |

